

## PRODUCT SPECIFICATION

Collection	GRAND CANYON	ANTIQUE	JUPITER XL	NATURAL WONDERS
Format	plank	herringbone / chevron	XL tile	XL plank
Overall thickness (ISO 24337)	2,0 mm	2,5 mm	2,5 mm	2,5 mm
Wear layer (EN 429)	0,30 mm		0,55 mm	
Tile / plank size (ISO 24337)	178 x 1219 mm	125 x 625 mm / 155 x 930 mm	609 x 609 mm / 457 x 914 mm	228 x 1828 mm
Total weight (ISO 23997)	3.900 g/m <sup>2</sup>	4.900 g/m <sup>2</sup> / 4.350 g/m <sup>2</sup>	4.350 g/m <sup>2</sup>	4.900 g/m <sup>2</sup>
Construction	virgin base material			
Surface	regular wood	light wood	light stone	deep wood
Finish	EpuShield anti-scratch matte coating			
Installation	glue down			
Warranty	25 years residential 10 years commercial	25 years residential / 10 years commercial / 5 years industrial		

## PACKAGING INFORMATION

Collection	GRAND CANYON	ANTIQUE	JUPITER XL	NATURAL WONDERS
Pieces per box	18	18 / 27	12 / 12	10
Area per box (m <sup>2</sup> )	3,910	1,410 / 3,900	4,450 / 5,012	4,170
Weight per box (kg)	16,01	7,60 / 17,66	20,37 / 22,23	17,10

## ADVANCED TECHNICAL DATA

Fire resistance	EN 13501-1		Bfl-s1
Formaldehyde emission	EN 14041		E1
Slip resistance	EN 13893		DS
	DIN 51130:2014		R10
Dimension stability	EN 434		≤ 0,15% (norm: ≤ 0,25%)
Wear group	23: domestic heavy		23: domestic heavy ; 33: commercial heavy
	33: commercial heavy		42: light industrial general
Abrasion resistance	EN 13329 Annex E		pass (≥ 4000 cycles)
Castor chair	EN 425		pass (no visible change)
Residual indentation	EN 434		pass (≤ 0,1 mm)
Stain resistance	EN 438		pass (grade 5)
UV resistance	ISO 105-B02		pass (≥ 6)
Thermal conductivity	EN 12524		0,25 W / m K
Thermal resistance	EN 12524		0,012 (m <sup>2</sup> K) / W
Underfloor heating			suitable for underfloor heating under certain conditions
Acoustic insulation	EN ISO 717-2		ΔLw 3 dB