

MEISTER Twin Control is an insulating underlay with an integrated vapour barrier for loose laying under MeisterParquet, longlife, Lindura wood flooring and laminate flooring.

General data

Dimensions:	Width:	approx. 1 m
	Length:	approx. 25 m
Thickness:	ca. 2 mm	
Weight per unit area:	ca. 0.3 kg/m ²	

Technical data

Product composition:	Insulating underlay made of closed-cell, extruded polyethylene foam with LDPE-foam and an integrated self-adhesive strip along its length.
(CS) - Compressive Strength (EN 826):	≥ 60 kPa
(IS) - Impact Sound Reduction (EN ISO 10140-3) under 7 mm laminate flooring:	up to 19 dB
(R) - Thermal Resistance (EN 12 667 or EN 12 664):	approx. 0.045 m ² × K/W
Underfloor heating:	Suited to a certain extent for installation on underfloor heating.
(RTF) - Fire behaviour (EN 13 501):	E _{fl}
(DL ₂₅) - Dynamic Load (EN 13 793):	> 150,000 cycles
(SD) - Water vapor diffusion resistance (EN 12 086):	S _d > 100 m
(PC) - Punctual Conformability (EN ISO 868):	1.2 mm
(RLB) - Resistance to Large Ball (EN 13 329):	1200 mm
(CC) - Compressive Creep (EN 1606):	≥ 10 kPa

General data on environment and installation

Environment:	The following substances are not contained in the product: Halogens Plastic softeners Solvents Asbestos Formaldehyde
Installation:	Lay with white foam sheeting up, and place it with the side without adhesive tape on the wall. Glue all head joints with aluminium tape. No additional PE film required. Please note the flooring manufacturer's requirements with regard to the underlay.
Disposal:	Fully recyclable, disposal in normal household waste

