

GENERAL DATA

Width	180	mm
Length	1220	mm
Thickness	6.00 (underlay included)	mm
Top layer	0.55	mm
Bevels	4-sided micro (with pressed in bevel all around)	
Tongue and groove	click Välinge 2G	
m ² per pack	2.200	m ²
Number of panels per pack	10	pcs
Underlay IXPE (included)	1.0	mm

FACTORY WARRANTY

Usage Class	EN 13329	23 / 33
CE	EN 14041	
Residential use	25	years
Commercial use	10	years
Country of origin	Made in China	

DETAILED DATA

m ² per pack	2.200	m ²
m ² per pallet	110.00	m ²
m ² per container	2.200	m ²
Weight per pack	21.00	kg
Weight per pallet	1050.0	kg
Package width	182.0	mm
Package length	1222.0	mm
Package thickness	62.0	mm
Total weight	9.500	g / m ² (rigid composite vinyl)
Anti-slip	DIN 51130:2014: R10	
Thermal resistance (EN 12524)	0.055	m ² K/W (floor + underlay)
Thermal conductivity (EN 12524)	1,09	W/mK (floor + underlay)
Dimensional stability	EN 427: length max 0.5 mm	EN 428: average thickness +/- 0.2 mm EN 434: max. 0.25% (on average < 0.1%)
Formaldehyde emissions	E1	
Sound absorption	EN ISO 10140-3: ΔLw 19 dB	

INSTALLATION

Method	floating, glueless
Floor heating	Suitable for all standard heating systems in cement floors. Limited use with heating films and alternatives. Max. contact temperature ≤ 27 °C.